

TAYO

CCTV SYSTEM



CS-CIR68 彩色防水型紅外線攝影機(12IR)

■ SPECIFICATIONS

Model	NTB2111NDA17 NTB2111PDA17
Image Pick-up Device	SHARP1/3" CCD Normal Resolution
Effective Picture Elements	NTSC:510*492,PAL:500*582 (H*V)
Horizontal Resolution	380 TV lines
Minimum Illumination	IR"ON"與 IR cut "Use" = 0LUX /6mmF2.0
S/N Ratio	More than 48 dB
Auto Electronic Shutter	NTSC:1/60s~1/100,000s, PAL:1/50s~1/110,000s
Gamma Characteristic	0.45
Lens Furnished	Board lens :6mm / F2.0(optional: 6.0/8.0mm)
Gain Control	Automatically
White Balance	Automatically (2500K~9500K)
Synchronous System	Negative sync. Internal
Video Output	1.1 Vp-p Composite Video / 75 Ohms.
Power Supply	DC 12V +/- 1V
Power Consumption	DC12V Typical 85mA, IR"ON" Total 220mA
Operating Temp.	-10°C to 50°C (14°F to 122°F)
Dimensions	153(L)*76.5(W)*65(H) mm

總代理:帝谷通信工程有限公司