



Compression Card Comparison Chart (Single Card)

	GV-600 A	GV-650 A	GV-800 A	GV-600 B	GV-650 B	GV-800 B	GV-900 A	GV-1008	GV-1120 A	GV-1240 A	GV-1480 A	GV-1120 B	GV-1240 B	GV-1480 B	GV-3008	GV-4008 A	GV-5016		
Interface	PCI	PCI, PCI-E (x1)		PCI-E (x1)								PCI-E (x4)				PCI-E (x1)			
Input Type	BNC, D-Type	BNC, D-Type	BNC, D-Type	DVI				D-Type, DVI				DVI			D-Type	DVI	LFH		
Video Input	1, 2, 4, 6, 8, 10, 12, 14, 16	4, 8, 12, 16		4, 8, 16			8, 16, 32	8	8, 12, 16	8, 16	16	16				8	16		
Recording Rate	CIF	NTSC	30 fps	60 fps	120 fps	4 port: 30 fps 16 port: 30 fps	4 port: 60 fps 16 port: 60 fps	4 port: 120 fps 16 port: 120 fps	8 port: 240 fps 32 port: 240 fps	240 fps	120 fps	240 fps	480 fps	120 fps	240 fps	480 fps	-	-	
		PAL	25 fps	50 fps	100 fps	4 port: 25 fps 16 port: 25 fps	4 port: 50 fps 16 port: 50 fps	4 port: 100 fps 16 port: 100 fps	8 port: 200 fps 32 port: 200 fps	200 fps	100 fps	200 fps	400 fps	100 fps	200 fps	400 fps	-	-	
	D1	NTSC	15 fps	30 fps	60 fps	4 port: 30 fps 16 port: 15 fps	4 port: 60 fps 16 port: 30 fps	4 port: 120 fps 16 port: 60 fps	8 port: 240 fps 32 port: 120 fps	240 fps	80 fps	120 fps	240 fps	120 fps	240 fps	480 fps	240 fps	480fps	
		PAL	12.5 fps	25 fps	50 fps	4 port: 25 fps 16 port: 12.5 fps	4 port: 50 fps 16 port: 25 fps	4 port: 100 fps 16 port: 50 fps	8 port: 200 fps 32 port: 100 fps	200 fps	72 fps	100 fps	200 fps	100 fps	200 fps	400 fps	200 fps	400fps	
Display Rate	CIF	NTSC	30 fps	60 fps	120 fps	4 port: 30 fps 16 port: 30 fps	4 port: 60 fps 16 port: 60 fps	4 port: 120 fps 16 port: 120 fps	8 port: 240 fps 32 port: 240 fps	240 fps	480 fps	480 fps	480 fps	480 fps	480 fps	480 fps	-	-	
		PAL	25 fps	50 fps	100 fps	4 port: 25 fps 16 port: 25 fps	4 port: 50 fps 16 port: 50 fps	4 port: 100 fps 16 port: 100 fps	8 port: 200 fps 32 port: 200 fps	200 fps	400 fps	400 fps	400 fps	400 fps	400 fps	400 fps	-	-	
	D1	NTSC	15 fps	30 fps	60 fps	4 port: 30 fps 16 port: 15 fps	4 port: 60 fps 16 port: 30 fps	4 port: 120 fps 16 port: 60 fps	8 port: 240 fps 32 port: 120 fps	240 fps	480 fps	480 fps	480 fps	480 fps	480 fps	480 fps	240 fps	480 fps	
		PAL	12.5 fps	25 fps	50 fps	4 port: 25 fps 16 port: 12.5 fps	4 port: 50 fps 16 port: 25 fps	4 port: 100 fps 16 port: 50 fps	8 port: 200 fps 32 port: 100 fps	200 fps	400 fps	400 fps	400 fps	400 fps	400 fps	400 fps	200 fps	400 fps	
Video Codec	Geo MPEG4, Geo H.264														H/W: Geo H.264 S/W: Geo MPEG4, Geo H.264				
Video Resolution	NTSC	704 x 480, 704 x 480 De-interlace, 640 x 480, 640 x 480 De-interlace, 352 x 240, 320 x 240																	
	PAL	704 x 576, 704 x 576 De-interlace, 640 x 480, 640 x 480 De-interlace, 352 x 288, 320 x 240																	
Audio Input	1	2	4				8		8, 12, 16	8, 16	16				8	16			
Audio Codec	AAC (16 kHz / 16 bit)																		
GV-Multi Quad Card Support	○	○	○	✗	✗	✗	✗	○	○	○	○	○	○	○	○	○	✗		
GV-Loop Through Card Support	○	○	○	✗	✗	✗	✗	○	○	○	○	○	○	○	○	○	✗		
GV-NET/I/O Card Support	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○ ¹	○ ¹		
GV-I/O 12-In Card Support	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○ ¹	○ ¹		
GV-I/O 12-Out Card Support	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○ ¹	○ ¹		
Hardware Watchdog	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○		
Dimensions (W x H)	144 X 89 mm	174 x 98 mm	BNC: 152 x 94 mm; D-Type: 174 x 98 mm	PCI-E: 120 x 82 mm				120 X 112 mm	179 X 99 mm	179 X 112 mm			156 X 111 mm				180 x 112 mm	169 x 112 mm	168 x 70 mm
Minimum System Requirements																			
OS	Windows XP (32-bit) / Vista (32-bit) / 7 (32-bit and 64-bit) / Server 2008 (32-bit and 64-bit)																		
DirectX	9.0c																		
CPU	Pentium 4, 2.0 GHz	Pentium 4, 2.4 GHz	Pentium 4, 3.0 GHz with HT	Pentium 4, 2.0 GHz	Pentium 4, 2.4 GHz	Pentium 4, 3.0 GHz with HT	Pentium 4, 3.0 GHz Dual Core	Core 2 Duo, 3.0 GHz	Pentium 4, 3.0 GHz With HT	Pentium 4, 3.0 GHz Dual Core	Core 2 Duo, 3.0 GHz	Pentium 4, 3.0 GHz With HT	Pentium 4, 3.0 GHz Dual Core	Core 2 Duo, 3.0 GHz	Core 2 Duo, 2.33 GHz	Core 2, Quad 2.4 GHz			
RAM	2 x 512 MB Dual Channels (Windows XP)						2 x 1 GB Dual Channels	2 x 512 MB Dual Channels (Windows XP)				2 x 512 MB Dual Channels (Windows XP)			2 x 1 GB Dual Channels				
	2 x 1 GB Dual Channels (Windows Vista / 7 / Server 2008)							2 x 1 GB Dual Channels (Windows Vista / 7 / Server 2008)				2 x 1 GB Dual Channels (Windows Vista / 7 / Server 2008)							
HDD	80 GB						160 GB	250 GB	80 GB	120 GB	250 GB	80 GB	120 GB	250 GB	250 GB	500 GB			
Graphic Card	AGP or PCI-Express, 800 x 600 (1280 x 1024 recommended), 32-bit color																		

Note:

- GV-1120A/1240A/1480A cards support TV-Out function. GV-1120B/1240B/1480B cards do not have a TV-Out port but you can use Digital Matrix function for multiple monitor displays.
- To work together with GV-4008A/5016, GV-NET I/O Card V3.1 must be set in the I/O Box Mode and connected to the PC through USB or DB9.
- All specifications are subject to change without notice.



Compression Card Comparison Chart (Two Cards)

		GV-600A X 2	GV-650A X 2	GV-800A X 2	GV-600B X 2	GV-650B X 2	GV-800B X 2	GV-900A X 2	GV-1008 A X 2	GV-1120 A X 2	GV-1240 A X 2	GV-1480 A X 2	GV-1120 B X 2	GV-1240 B X 2	GV-1480 B X 2	GV-3008 x 2	GV-4008 A X 2	GV-5016 x 2	
Interface		PCI x 2		PCI x 2, PCI-E (x1) x 2, PCI x 1 + PCI-E (x1) x 1	PCI-E (x1) x 2,			PCI-E (x1) x 2					PCI-E (x4) x 2			PCI-E (x1) x 2			
Input Type		BNC, D-Type	BNC, D-Type	BNC, D-Type	DVI			D-Type, DVI					DVI			D-Type	DVI	LFH	
Video Input		32 (Max.)			8, 12, 16, 20, 24, 32			16, 24, 32	16	16, 20, 24, 28, 32	16, 24, 32	32	32			16			32
Recording Rate	CIF	NTSC	60 fps	120 fps	240 fps	4+4 port: 60 fps 16+16 port: 60 fps	4+4 port: 120 fps 16+16 port: 120 fps	4+4 port: 240 fps 16+16 port: 240 fps	8+8 port: 480 fps 16+16 port: 480 fps	480 fps	240 fps	480 fps	960 fps	240 fps	480 fps	960 fps	-		
		PAL	50 fps	100 fps	200 fps	4+4 port: 50 fps 16+16 port: 50 fps	4+4 port: 100 fps 16+16 port: 100 fps	4+4 port: 200 fps 16+16 port: 200 fps	8+8 port: 400 fps 16+16 port: 400 fps	400 fps	200 fps	400 fps	800 fps	200 fps	400 fps	800 fps	-		
	D1	NTSC	30 fps	60 fps	120 fps	4+4 port: 60 fps 16+16 port: 30 fps	4+4 port: 120 fps 16+16 port: 60 fps	4+4 port: 240 fps 16+16 port: 120 fps	8+8 port: 480 fps 16+16 port: 240 fps	480 fps	160 fps	240 fps	480 fps	240 fps	480 fps	960 fps	480 fps	960fps	
		PAL	25 fps	50 fps	100 fps	4+4 port: 50 fps 16+16 port: 25 fps	4+4 port: 100 fps 16+16 port: 50 fps	4+4 port: 200 fps 16+16 port: 100 fps	8+8 port: 400 fps 16+16 port: 200 fps	400 fps	144 fps	200 fps	400 fps	200 fps	400 fps	800 fps	400 fps	800fps	
Display Rate	CIF	NTSC	60 fps	120 fps	240 fps	4+4 port: 60 fps 16+16 port: 60 fps	4+4 port: 120 fps 16+16 port: 120 fps	4+4 port: 240 fps 16+16 port: 240 fps	8+8 port: 480 fps 16+16 port: 480 fps	480 fps	960 fps	960 fps	960 fps	960 fps	960 fps	960 fps	-		
		PAL	50 fps	100 fps	200 fps	4+4 port: 50 fps 16+16 port: 50 fps	4+4 port: 100 fps 16+16 port: 100 fps	4+4 port: 200 fps 16+16 port: 200 fps	8+8 port: 400 fps 16+16 port: 400 fps	400 fps	800 fps	800 fps	800 fps	800 fps	800 fps	800 fps	-		
	D1	NTSC	30 fps	60 fps	120 fps	4+4 port: 60 fps 16+16 port: 30 fps	4+4 port: 120 fps 16+16 port: 60 fps	4+4 port: 240 fps 16+16 port: 120 fps	8+8 port: 480 fps 16+16 port: 240 fps	480 fps	960 fps	960 fps	960 fps	960 fps	960 fps	960 fps	480 fps	960 fps	
		PAL	25 fps	50 fps	100 fps	4+4 port: 50 fps 16+16 port: 25 fps	4+4 port: 100 fps 16+16 port: 50 fps	4+4 port: 200 fps 16+16 port: 100 fps	8+8 port: 400 fps 16+16 port: 200 fps	400 fps	800 fps	800 fps	800 fps	800 fps	800 fps	800 fps	400 fps	800 fps	
Video Codec		Geo MPEG4, Geo H.264														H/W: Geo H.264 S/W: Geo MPEG4, Geo H.264			
Video Resolution	NTSC	704 x 480, 704 x 480 De-interlace, 640 x 480, 640 x 480 De-interlace, 352 x 240, 320 x 240																	
	PAL	704 x 576, 704 x 576 De-interlace, 640 x 480, 640 x 480 De-interlace, 352 x 288, 320 x 240																	
Audio Input		2	4	8			16			16, 20, 24, 28, 32	16, 24, 32	32			16			32	
Audio Codec		AAC (16 kHz / 16 bit)																	
GV-Multi Quad Card Support		○	○	○	✗	✗	✗	✗	○	○	○	○	○	○	○	○	○	✗	
GV-Loop Through Card Support		○	○	○	✗	✗	✗	✗	○	○	○	○	○	○	○	○	○	✗	
GV-NET/I/O Card Support		○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○ ¹	○ ¹	
GV-I/O 12-In Card Support		○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○ ¹	○ ¹	
GV-I/O 12-Out Card Support		○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○ ¹	○ ¹	
Hardware Watchdog		○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	
		Minimum System Requirements																	
OS		Windows XP (32-bit) / Vista (32-bit) / 7 (32-bit and 64-bit) / Server 2008 (32-bit and 64-bit)																	
DirectX		9.0c																	
CPU		Pentium 4, 2.6 GHz with HT	Pentium 4, 2.8 GHz with HT	Pentium 4, 3.0 GHz Dual Core	Pentium 4, 2.6 GHz with HT	Pentium 4, 2.8 GHz with HT	Pentium 4, 3.0 GHz Dual Core	Core i5-750, 2.66 GHz	Pentium 4, 3.0 GHz Dual Core	Core 2 Duo, 2.53GHz	Core 2 Quad, 2.4GHz	Core 2 Duo, E7200, 2.53GHz	Core 2 Duo, 3.0GHz	Core 2 Quad, 2.4GHz	Core 2 Quad, 2.4GHz	Core 2 Quad, 2.4GHz	Core i5 650, 3.2GHz		
RAM		2 x 1 GB Dual Channels																	
HDD		160 GB			500 GB			160 GB	250 GB	500 GB	160 GB	250 GB	500 GB	500 GB	500 GB	500 GB	1 TB		
Graphic Card		AGP or PCI-Express, 800 x 600 (1280 x 1024 recommended), 32-bit color																	

Note:

- GV-1120A/1240A/1480A cards support TV-Out function. GV-1120B/1240B/1480B cards do not have a TV-Out port but you can use Digital Matrix function for multiple monitor displays.
- To work together with GV-4008A/5016, GV-NET I/O Card V3.1 must be set in the I/O Box Mode and connected to the PC through USB or DB9.
- All specifications are subject to change without notice.



Compression Card Comparison Chart (SDI Card)

		GV-SDI-204	GV-SDI-204 (x 4)
Interface		PCI-E (x1)	PCI-E (x1) x 4
Input Type		BNC	
Video Input		4	16
Recording Rate and Display Rate	1080p	NTSC	480 fps
		PAL	400 fps
	720p	NTSC	960 fps
		PAL	800 fps
	1080i	NTSC	480 fps
		PAL	400 fps
Video Codec		H.264 Geo MPEG4, Geo H.264	
Video Resolution	H/W	1080p	1920 x 1080
		720p	1280 x 720
	S/W	1080i	1920 x 1080
		1080p	960 x 540, 480 x 270
	S/W	720p	640 x 360
		1080i	960 x 540, 480 x 270
Audio Input		N/A	
Audio Codec		N/A	
GV-Multi Quad Card Support		X	
GV-Loop Through Card Support		X	
GV-NET/IO Card Support		O ¹	
GV-I/O 12-In Card Support		O ¹	
GV-I/O 12-Out Card Support		O ¹	
Hardware Watchdog		O	
Dimensions (W x H)		158 x 111 mm	
Minimum System Requirements			
OS Windows XP (32-bit) / Vista (32-bit) / 7 (32-bit and 64-bit) / Server 2008 (32-bit and R2, 64-bit)			
DirectX 9.0c			
CPU		Core 2 Duo, 2.00 GHz	Core i3, 3.40 GHz
RAM 2 x 1 GB Dual Channels			
HDD		500 GB	2 TB
Graphic Card AGP or PCI-Express, 800 x 600 (1280 x 1024 recommended), 32-bit color			

Note:

- To work together with GV-SDI-204, GV-NET I/O Card V3.1 must be set in the I/O Box Mode and connected to the PC through USB or DB9.
- All specifications are subject to change without notice.